





# PETAL

design by Moreno De Giorgio

LightSound is a system that has been created to meet the acoustic and visual comfort needs, and to create a wellness space in the professional world. The human factor and technology are the basic components for the creation of contemporary work spaces. This product intervenes to create the right lighting and acoustics by reducing noise and, at the same time, perfectly illuminating the area. The office wellness becomes one of the most important elements of the design. The world of work merges with hospitality, perception and comfort.




 2,70  
2,10

 150x88x6,5 CM  
0,08 M<sup>3</sup>



<b>Description</b>	Pendant/wall-mounted sound-absorbing panel. In the suspended version, it can be combined with the Cloak panel, Triangle and Easy lamps from the LightSound collection.
<b>Structure</b>	6 plastic hooks for the cable or for wall-/ceiling-mounting placed on the corners.
<b>Composition</b>	Thermoformed polyester upholstered in Trevira CS fabric in a variety of color options.
<b>Sound-absorbing</b>	Surface area: - 0,77 M2 (wall-/ceiling) - 1,54 M2 (suspended)  Variable sound absorption coefficient in third-octave band values: equal to or more than 1 at average frequencies (arranged in suspension). Reference standards UNI EN ISO 354, UNI EN ISO 11654.  Sound-level graph: Fig. 1

## Fabrics



\* colors available from stock. Production lead time for non-stock colors: 5 weeks exclusive of delivery time..

## Standards



Class 1 Curtains and Drapes



OEKO TEX N. 072150.O



M1



BS 5852 Crib N°5 using a CM  
Foam 35 Kg/cu.m.



B1 DIN 4102



1021 Part 1-2 using a CM  
Foam 35 Kg/cu.m.



Calif. Bull. 117, Section E, Part I



Q1 (OENORM 3800 PART 1)



B1 (OENORM B 3825)



Azimut serie Mirage

IMO RES.A. 688(17)-Bedding Components

IMO RES.A. 563(14)-Draperies, Curtains

IMO RES.A. 653(16)-Surface Materials  
and Floor Covering

IMO Res.A.652(16) FTP Code MSC 61

(67) Annex 1 Part 8 - Flame Retardant,

polyurethane flexible foam, nominal

density 35Kg/mq. in class 1 IM according

to UNI 9175 supplied by the Laboratory.




Fig. 1

LightSound  
PETAL

SPECIFICATION  
SHEET